

**NovaSeal**<sup>®</sup>  
by **Tuck**



# NOVASEAL<sup>®</sup> PRO

## SYNTHETIC ROOF UNDERLAYMENT

NovaSeal<sup>®</sup> PRO is made from a completely waterproof construction of woven polypropylene and a slip resistant non-woven top surface. PRO forms a barrier in your roofing system that helps protect residential steep slope roofs in the most extreme weather conditions. PRO synthetic roof underlayment delivers exceptional long-term weather barrier performance compared to traditional asphalt felt products.

PRO is designed for use under asphalt and synthetic shingles, metal in residential applications and primed cedar shakes.



One 10 square roll = 5 felt rolls!

## FEATURES & BENEFITS




Lightweight  
10-square roll = 18 lbs



Non-woven surface  
is slip resistant



Requires fewer  
fasteners than typical  
asphalt felt products




Horizontal marker  
for overlap



UV protection for  
up to 90 days



No special tools  
required



Greater roof  
coverage per roll



Tear & puncture  
resistant



800-565-2000 | [roofunderlayment.com](http://roofunderlayment.com)



## PROPERTIES / TEST METHOD

Product SKU	YIPGNPRO481A
Tensile Strength ASTM D5034	MD 100 lbs (45 kg) / CD 95 lbs (43 kg)
Tear Strength ASTM D4533	MD 25 lbs (11 kg) / CD 24 lbs (10.8 kg)
Liquid Water Transmission ASTM D4869	Pass
UV Exposure	90 Days
Permeability ASTM E96	< 0.05 Perms
Temperature Range	-40°F to 240°F / -40°C to 115°C
Limited Warranty	20 Years

## ROLL / PALLET SPECS

Length per Roll	250' / 76.2 m
Width per Roll	48" / 1.1 m
Weight per Roll	18 lbs / 8.1 kg
Roll Size	10 sq / 93 m <sup>2</sup>
Rolls per Pallet / Truck	64 / 2112

NovaSeal® PRO meets or exceeds all required building codes:

- ASTM D8257, ASTM D226 Types I & II, ASTM D4869
- CAN/CSA A123.3, CAN/CSA A220.1
- Florida Building Code FL26367
- Class A Fire ASTM E108
- CCRR 1105, AC188
- Texas Department of Insurance
- Miami-Dade County Approved



Scan for more info or visit [roofunderlayment.com](http://roofunderlayment.com)

